

	Model	Voltage	Dimensions - Inches (mm)			Weight lbs (kgs)	A/H @ 20Hr Rate to 1.75	Terminal Type
			Length	Width	Height			
AGM	8AU1	12	7 3/4 (197)	5 1/8 (130)	7 1/4 (184)	24 (10.9)	32	T874
	8AU1H	12	8 5/16 (211)	5 1/8 (130)	7 1/4 (184)	24 (10.9)	32	T874
	8A22NF	12	9 3/8 (238)	5 1/2 (140)	9 1/4 (235)	38.5 (17.5)	55	T881
	8A24	12	10 7/8 (276)	6 3/4 (171)	9 7/8 (251)	53 (24)	79	T881
	8A27	12	12 3/4 (324)	6 3/4 (171)	9 7/8 (251)	63 (28.6)	92	T881
	8A31DT	12	12 15/16 (329)	6 3/4 (171)	9 3/8 (238)	69 (31.3)	105	5/16 Stud and Auto Post
	8A31	12	12 15/16 (329)	6 3/4 (171)	9 3/8 (238)	69 (31.3)	105	3/8 Stud
	8A4D	12	20 3/4 (527)	8 1/2 (216)	10 (254)	129 (58.5)	198	Auto Post
	8A8D	12	20 3/4 (527)	11 (279)	10 (254)	158 (71.7)	245	Auto Post
	8AGC2	6	10 1/4 (260)	7 1/8 (181)	10 7/8 (276)	69.5 (31.5)	190	5/16 Stud and Auto Post
Gel	8GU1	12	7 3/4 (197)	5 1/8 (130)	7 1/4 (184)	23.4 (10.6)	31.6	T874
	8GU1H	12	8 5/16 (211)	5 1/8 (130)	7 1/4 (184)	23.4 (10.6)	31.6	T874
	8G40C	12	7 1/4 (184)	6 5/8 (168)	6 7/8 (175)	31.7 (14.4)	40	1/4" Female Insert
	8G22NF	12	9 3/8 (238)	5 1/2 (140)	9 1/4 (235)	37 (16.8)	50.9	T881
	8G34R	12	10 3/16 (258)	6 5/8 (168)	7 (178)	41.5 (18.8)	60	1/4" Female Insert
	8G24SS	12	10 1/4 (260)	6 3/4 (171)	8 1/4 (210)	52 (23.6)	73.6	1/4" Female Insert
	8G24M	12	10 7/8 (276)	6 3/4 (171)	9 7/8 (251)	52 (23.6)	73.6	T872M
	8G24T881	12	10 7/8 (276)	6 3/4 (171)	9 7/8 (251)	52 (23.6)	73.6	T881
	8G27	12	12 3/4 (324)	6 3/4 (171)	9 7/8 (251)	62.7 (28.5)	86.4	T881
	8G31DT	12	12 15/16 (329)	6 3/4 (171)	9 3/8 (238)	70 (31.8)	97.6	5/16 Stud and Auto Post
	8G31LS	12	12 15/16 (329)	6 3/4 (171)	9 3/8 (238)	69.5 (31.5)	97.6	3/8 Stud
	8G5SHP	12	13 29/50 (345)	6 5/8 (168)	11 (280)	85 (38.6)	125	Auto Post
	8G4D	12	20 3/4 (527)	8 1/2 (216)	10 (254)	127 (57.7)	183	Auto Post
	8G8D	12	20 3/4 (527)	11 (279)	10 (254)	157 (71.4)	225	Auto Post
	8GGC2	6	10 1/4 (260)	7 1/8 (181)	10 7/8 (276)	68.4 (31.1)	180	5/16 Stud and Auto Post