

| | ENERGY | | | | | | POWER | | | HIGH TEMPERATURE | |
|-----------------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|------------------|---------------|
| | LS 14250 | LS 14500 | LS 17330 | LS 17500 | LS 26500 | LS 33600 | LSH 14 Light | LSH 14 | LSH 20 | LSH 20-HTS | LSH 20-150 |
| Cell size | 1/2 AA | AA | 2/3 A | A | C | D | C | C | D | D | D |
| Cell construction | Bobbin | Bobbin | Bobbin | Bobbin | Bobbin | Bobbin | Spiral | Spiral | Spiral | Spiral | Spiral |
| Nominal voltage | 3.6 V | 3.6 V | 3.6 V | 3.6 V | 3.6 V | 3.6 V | 3.6 V | 3.6 V | 3.6 V | 3.6 V | 3.6 V |
| Nominal capacity | 1.2 Ah | 2.6 Ah | 2.1 Ah | 3.6 Ah | 7.7 Ah | 17.0 Ah | 3.6 Ah | 5.8 Ah | 13.0 Ah | 11.0 Ah | 14.0 Ah |
| Max. continuous current | 35 mA | 50 mA | 25 mA | 100 mA | 150 mA | 250 mA | 1.3 A | 1.3 A | 1.8 A | 1.0 A | 300 mA |
| Max. pulse discharge rate | 0.1 A | 0.25 A | 0.12 A | 0.25 A | 0.3 A | 0.4 A | 2.0 A | 2.0 A | 4.0 A | 3.0 A | 0.5 A |
| Max. outside diameter | 14.55 mm | 14.55 mm | 16.5 mm | 17.13 mm | 26.0 mm | 33.4 mm | 26.0 mm | 26.0 mm | 33.4 mm | 33.4 mm | 32.05 mm |
| Max. height | 25.15 mm | 50.3 mm | 33.4 mm | 50.9 mm | 50.4 mm | 61.6 mm | 50.4 mm | 50.4 mm | 61.6 mm | 61.6 mm | 61.7 mm |
| Operating temperature range | - 60 / +85°C | - 60 / +85°C | - 60 / +85°C | - 60 / +85°C | - 60 / +85°C | - 60 / +85°C | - 60 / +85°C | - 60 / +85°C | - 60 / +85°C | - 60 / +85°C | - 40 / +150°C |

Typical values relative to cells stored for one year or less at +30°C max ; Performances vary according to discharge characteristics (current, duration, frequency), temperature conditions, storage conditions prior to usage and applications acceptable minimum voltage.

abs