

Exide type designation	Type designation acc. to DIN 40742	Part number	Nominal voltage	Nominal capacity C10 1.8 V/C 20°C	Discharge current I10	Length (l)	Width (b/w1)	Width, incl. terminal+ connector (b/w2)	Height (h)	Installed length (B/L)	Weight	Internal resistance acc. to IEC 896-2	Short circuit current acc. to IEC 896-2	Terminal	Pole pairs
			V	Ah	A	max. mm	max. mm	max. mm	max. mm	mm	approx. kg	m Ω	A		
A602/200 WE	4 OPzV 200 WE	NGA6020200HS0FB	2	200	20	105	360	398	208	113	20	0.94	2235	F-M8	1
A602/250 WE	5 OPzV 250 WE	NGA6020250HS0FB	2	250	25	126	360	398	208	134	23	0.78	2706	F-M8	1
A602/300 WE	6 OPzV 300 WE	NGA6020300HS0FB	2	300	30	147	360	398	208	155	27	0.60	3414	F-M8	1
A602/350 WE	5 OPzV 350 WE	NGA6020350HS0FB	2	350	35	126	475	513	208	134	30	0.61	3418	F-M8	1
A602/420 WE	6 OPzV 420 WE	NGA6020420HS0FB	2	420	42	147	475	513	208	155	35	0.49	4220	F-M8	1
A602/490 WE	7 OPzV 490 WE	NGA6020490HS0FB	2	490	49	168	475	513	208	176	40	0.51	4096	F-M8	1
A602/600 WE	6 OPzV 600 WE	NGA6020600HS0FB	2	600	60	147	650	688	208	155	48	0.44	4743	F-M8	1
A602/800 WE	8 OPzV 800 WE	NGA6020800HS0FB	2	800	80	193	650	688	212	203	67	0.30	6818	F-M8	2
A602/1000 WE	10 OPzV 1000 WE	NGA6021000HS0FB	2	1000	100	235	650	688	212	245	80	0.25	8200	F-M8	2
A602/1200 WE	12 OPzV 1200 WE	NGA6021200HS0FB	2	1200	120	277	650	688	212	287	94	0.21	9840	F-M8	2
A602/1500 WE	12 OPzV 1500 WE	NGA6021500HS0FB	2	1500	150	277	800	838	212	287	118	0.19	10500	F-M8	2