

Type	Part number	Nom. voltage	Nominal capacity C120 1.85 Vpc	Discharge current I120	Length (l)	Width (b/w)	Height up to top of cover (h1)	Height incl. connectors (h2)	Weight	Terminal	Pole pairs
		V	Ah	A	max. mm	max. mm	max. mm	max. mm	approx. kg		
4 OPzV 240	NGS6020240HS0FA	2	294	2.45	105	208.0	357.0	399.0	19.00	F-M8	1
5 OPzV 300	NGS6020300HS0FA	2	367	3.05	126	208.0	357.0	399.0	23.00	F-M8	1
6 OPzV 360	NGS6020360HS0FA	2	440	3.66	147	208.0	357.0	399.0	27.00	F-M8	1
5 OPzV 400	NGS6020400HS0FA	2	519	4.32	126	208.0	473.0	515.0	30.00	F-M8	1
6 OPzV 500	NGS6020500HS0FA	2	623	5.19	147	208.0	473.0	515.0	35.00	F-M8	1
7 OPzV 600	NGS6020600HS0FA	2	727	6.05	168	208.0	473.0	515.0	39.00	F-M8	1
6 OPzV 720	NGS6020720HS0FA	2	848	7.06	147	208.0	648.0	690.0	49.00	F-M8	1
8 OPzV 960	NGS6020960HS0FA	2	1131	9.42	212	193.0	648.0	690.0	66.00	F-M8	2
10 OPzV 1200	NGS6021200HS0FA	2	1413	11.70	212	235.0	648.0	690.0	80.00	F-M8	2
12 OPzV 1400	NGS6021400HS0FA	2	1695	14.10	212	277.0	648.0	690.0	95.00	F-M8	2
12 OPzV 1700	NGS6021700HS0FA	2	1959	16.30	212	277.0	798.0	840.0	117.00	F-M8	2
16 OPzV 2300	NGS6022300HS0FA	2	2613	21.70	216	400.0	775.0	816.0	160.00	F-M8	3
20 OPzV 2900	NGS6022900HS0FA	2	3266	27.20	214	489.0	774.0	816.0	198.00	F-M8	4
24 OPzV 3500	NGS6023500HS0FA	2	3919	32.60	214	578.0	774.0	816.0	238.00	F-M8	4